

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number
WO 2004/055241 A3

(51) International Patent Classification⁷:
G01N 33/18, 27/62

C25B 1/04,

(72) Inventors; and

(21) International Application Number:

PCT/JP2003/015999

(75) Inventors/Applicants (for US only): YOSHIDA, Naohiro [JP/JP]; C/O Tokyo Institute of Technology, 12-1, O-okayama 2-Chome, Meguro-ku, Tokyo 152-8550 (JP). ABE, Osamu [JP/JP]; C/O Hydrospheric Atmospheric Research Center, Nagoya University, Furo-cho, Chikusa-ku, Nagoya-shi, Aichi 464-8601 (JP). UEMURA, Ryu [JP/JP]; C/O Tokyo Institute of Technology, 12-1, O-okayama 2-Chome, Meguro-ku, Tokyo 152-8550 (JP). WATANABE, Hiroshi [JP/JP]; C/O SUGA TEST INSTRUMENTS CO., LTD., 4-14, Shinjuku 5-Chome, Shinjuku-ku, Tokyo 160-0022 (JP).

(22) International Filing Date:

12 December 2003 (12.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2002-361726 13 December 2002 (13.12.2002) JP


(74) Agent: FURUYA, Fumio; Dai2 Meiho Bldg., 9th Floor, 19-5, Nishishinjuku 1-Chome, Shinjuku-ku, Tokyo 160-0023 (JP).

(71) Applicants (for all designated States except US): SUGA TEST INSTRUMENTS CO., LTD. [JP/JP]; 4-14, Shinjuku 5-Chome, Shinjuku-ku, Tokyo 160-0022 (JP). JAPAN SCIENCE AND TECHNOLOGY AGENCY [JP/JP]; 1-8, Honcho 4-Chome, Kawaguchi-shi, Saitama 332-0012 (JP). THE CIRCLE FOR THE PROMOTION OF SCIENCE AND ENGINEERING [JP/JP]; 12-1, O-okayama 2-Chome, Meguro-ku, Tokyo 152-8550 (JP).

(81) Designated States (national): AE, AG, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LU, MA, MD, MG, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: WATER ELECTROLYSIS METHOD AND DEVICE FOR DETERMINATION OF HYDROGEN AND OXYGEN STABLE ISOTOPIC COMPOSITION



(57) Abstract: To provide a water electrolysis device for the determination of stable isotopic composition of water and a water electrolysis method for stable isotopic composition of water capable of analyzing many samples with ease, with safety and at low cost in a very short time, and rapidly analyzing ¹⁷O. The water electrolysis device performing mass spectrometry of hydrogen or oxygen stable isotopic composition includes: a proton exchange membrane which is made of fluorocarbon polymer plated non-electrolytically with platinum, iridium, rhodium or iridium-rhodium alloy, and a cathode and an anode made of porous titanium plated with platinum and sandwiching the proton exchange membrane, in which water is electrolyzed by introducing it into the anode side chamber and supplying a DC current between the anode and the cathode, and oxygen gas generated at the anode and hydrogen gas generated at the cathode are respectively allowed to flow into a isotope ratio mass spectrometer. Also it is provided that a water electrolysis method for stable isotopic composition of water using the water electrolysis device.